

AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386

CLAIM AMENDMENTS:

1. (Original) A portable communication device comprising:
an analog-to-digital converter to provide a digital output signal;
a signal generator coupled to the digital output signal to generate a feedback signal; and
wherein the portable communication device is adapted to subtract the feedback signal
from an intermediate frequency (IF) signal.
2. (Original) The portable communication device of claim 1, further comprising a filter
adapted to provide a filtered signal with a bandwidth, wherein the signal generator
generates a feedback signal that reduces the difference between the IF signal and the
feedback signal over at least a portion of the bandwidth of the filtered signal.
3. (Original) The portable communication device of claim 2, wherein the portable
communication device is adapted to change the digital output signal to reduce the
difference between the IF signal and the feedback signal.
4. (Original) The portable communication device of claim 2, further comprising a
multiplier coupled to an integrator, wherein the multiplier is adapted to multiply a local
oscillator signal and the filtered signal.

AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386

5. (Original) The portable communication device of claim 1, wherein the signal generator comprises a modulator.

6. (Original) The portable communication device of claim 5, wherein the signal generator comprises an amplitude shift key modulator.

7. (Original) The portable communication device of claim 5, further comprising a local oscillator coupled to the modulator.

8. (Original) The portable communication device of claim 7, wherein the digital output signal consists of a bit coupled to the signal generator such that the signal generator generates a feed back signal that is either in-phase with the local oscillator or about 180° out of phase with the local oscillator.

9. (Original) The portable communication device of claim 7, wherein the digital output signal comprises at least two bits.

**AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386**

10. (Original) The portable communication device of claim 1, wherein the portable communication device is adapted to receive an input signal and the digital output signal represents an over-sampled version of the input signal.

11. (Original) An apparatus comprising:

a subtractor adapted to subtract a feedback signal from an intermediate frequency (IF) to provide a subtracted signal; and

a signal generator to provide the feedback signal determined, at least in part, on the subtracted signal.

12. (Original) The apparatus of claim 11, further comprising an integrator coupled to receive the subtracted signal.

13. (Original) The apparatus of claim 11, further comprising a multiplier to multiply the subtracted signal with a signal from an oscillator.

AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386

14. (Original) The apparatus of claim 11, further comprising an analog-to-digital converter to provide a digital output signal, wherein the feedback signal is determined, at least in part, on the digital output signal.

15. (Original) The apparatus of claim 11, wherein the signal generator comprises a modulator.

16. (Original) The apparatus of claim 15, wherein the modulator is coupled to a local oscillator.

17. (Original) The apparatus of claim 11, further comprising an antenna adapted to receive a radio frequency (RF) signal.

18. (Original) The apparatus of claim 17, wherein the RF signal is the IF signal.

19. (Currently amended) A method comprising:

receiving an input intermediate frequency (IF) signal and generating a quantized signal determined, at least in part, on the input IF signal; and

AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386

subtracting a feedback signal from the input IF signal to provide a subtracted signal.

20. (Original) The method of claim 19, further comprising generating the feedback signal with the quantized signal.

21. (Original) The method of claim 20, wherein generating a quantized signal includes converting a signal with an analog-to-digital converter to provide a digital output signal.

22. (Original) The method of claim 21, further comprising modulating the digital output signal to provide the feedback signal.

23. (Original) The method of claim 19, further comprising integrating the subtracted signal.

24. (Original) The method of claim 19, further comprising multiplying the subtracted signal with a signal generated from an oscillator.

AMENDMENT under 37 C.F.R. § 1.111
U.S. Appl. No. 09/750,386

25. (Currently amended) An article comprising: a storage medium having stored thereon instructions, that, when executed by a computing platform, result in:
receiving an input intermediate frequency (IF) signal and generating a quantized signal determined, at least in part, on the input IF signal; and
subtracting a feedback signal from the input IF signal to provide a subtracted signal.

26. (Original) The article of claim 25, wherein the instructions, when executed, further result in converting a signal with an analog-to-digital converter to provide a digital output signal.

27. (Original) The article of claim 25, wherein the instructions, when executed, further result in integrating the subtracted signal.